



- Weldable stud range 13 – 22 mm
- Ideal for KÖCO stud welding equipment ELOTOP 2002
- Adjustable plunge damper
- Robust housing
- Suitable for welding on building site

Technical data

Stud welding with ceramic ferrule Weldable stud range \varnothing (mm)	13 - 22
Compensation for stud length variations up to ... (mm)	8
Standard support with ...legs	2
Lifting range from ... to ... (mm)	2,5 - 6
Input voltage lifting coil (V=)	60 - 90
Welding cable (m/mm ²)	2/95
Welding cable plug (mm ²)	95
Control cable (m/mm ²)	2/4 x 1,0
Length (excluding chuck) (mm)	250
Body \varnothing approx. (mm)	60
Height (including handle) (mm)	220
Weight excluding cables app. (kg)	1,4

Description

The model K 24 is a robust stud welding gun, especially for studs \varnothing 19 - 22 mm

Ideal for welding shear connectors

Ideal for through-deck-welding TD

High repeatability

Compensation for stud length variations up to 8 mm

Hydraulic plunge damper

Supported by 2 legs

Body made of fibre-glass reinforced polyamide

Adjustable hydraulic plunge damper for studs from app. \varnothing 14 mm

Lifting ring system with length compensation

Control cable plug (4 wire)